

PRODUCT ORDERING GUIDE


Eliminator Series SP

316 STAINLESS STEEL



Custom products are available.

Contact sales@edriveactuators.com with your requirements.

BASE NUMBER		OPTIONS				SPECIAL													
S	P																		
Base No. (Capacity)		Unit Mounting Option				Motor Position				Custom Length (in)				Precision/Lead Accuracy***					
SP201 (1,000 lbf) SP302 (2,000 lbf) SP304 (4,000 lbf) SP404 (4,000 lbf) SP406 (6,000 lbf) SP508 (8,000 lbf) SP516 (16,000 lbf) SP618 (18,000 lbf) SP625 (25,000 lbf)		MB: Bottom Mount FF: Front Flange MF: Foot Mount TF: Front Trunnion				1, 2, 3, 4 0 = In-Line 				00.00				A: .002 in/ft Zero Backlash B: .0005 in/ft Zero Backlash X: Standard					
Std. Stroke Length*		Rod End Option ****				Gearbelt Reduction				N.C. Switch Qty ****				N.O. Switch Qty ****					
06: 6 in. 12: 12 in. 18: 18 in. 24: 24 in. 30: 30 in. 36: 36 in. 42: 42 in. 48: 48 in.		E: Female Eye F: Female Thread A: Self-Aligning Coupler** M: Male Thread S: Spherical Rod Eye				00: In-Line/Direct Coupled 10: 1:1 20: 2:1				0, 1, 2, 3, etc.				0, 1, 2, 3, etc.					
		Configuration				Switch Type													
		L: In-Line U: Parallel Offset				A: Hall Sourcing PNP B: Hall Sinking NPN C: Reed X: No Switches													

* Standard Stroke Lengths
 SP201 stroke lengths up to 12 in.
 SP302 – SP304 stroke lengths up to 36 in.
 SP404 – SP406 stroke lengths up to 42 in.
 SP508 – SP625 stroke lengths up to 48 in.

** Self-Aligning Coupler
 Not available for SP625
 *** Precision/Lead Accuracy
 SP201 – 0.0005 in/ft, Zero Backlash is standard
 SP302, SP404 – Zero Backlash not available

**** IP69K Exceptions
 Self-Aligning Coupler and Spherical Rod Ends not rated
 Sealed Limit Switches, IP65 rated

For applications support contact us today.

sales@edriveactuators.com

FB6103

EDrive Actuators, Inc.
 385 Stamm Rd.
 Newington, CT 06111

Website: edriveactuators.com
 Phone: 1.860.953.0588
 Fax: 1.860.953.0496

© 2020 all rights reserved