

## PRODUCT ORDERING GUIDE


# Eliminator Series SDL

SUPER DUTY WITH LOAD CELL



Custom products are available.

Contact [sales@edriveactuators.com](mailto:sales@edriveactuators.com) with your requirements.

BASE NUMBER				OPTIONS				SPECIAL											
<b>S</b>	<b>D</b>	<b>L</b>																	
<b>Base No. (Capacity)</b> <b>SDL 930</b> (30,000lbf) <b>SDL 948</b> (48,000lbf) <b>SDL 966</b> (66,000 lbf) <b>SDL 999</b> (100,000 lbf)				<b>Unit Mounting Option</b> <b>MB:</b> Bottom Mount <b>FF:</b> Front Flange <b>MF:</b> Foot Mount				<b>Motor Position</b> 1, 2, 3, 4 0 = In-Line 				<b>Custom Length (in)</b> 00.00							
<b>Std. Stroke Length</b> <b>06:</b> 6 in. <b>12:</b> 12 in. <b>18:</b> 18 in. <b>24:</b> 24 in. <b>30:</b> 30 in. <b>36:</b> 36 in. <b>42:</b> 42 in. <b>48:</b> 48 in.				<b>Rod End Option</b> <b>E:</b> Female Eye <b>F:</b> Female Thread <b>A:</b> Self-Aligning Coupler <b>M:</b> Male Thread <b>S:</b> Spherical Rod Eye				<b>Gearbelt Reduction</b> <b>00:</b> In-Line/Direct Coupled <b>10:</b> 1:1 <b>20:</b> 2:1				<b>N.C. Switch Qty</b> 0, 1, 2, 3, etc.							
				<b>Configuration</b> <b>L:</b> In-Line <b>U:</b> Parallel Offset				<b>Switch Type</b> <b>A:</b> Hall Sourcing PNP <b>B:</b> Hall Sinking NPN <b>C:</b> Reed <b>D:</b> Switch Tracks Only / No Switches <b>X:</b> Solid Cover / No Switches				<b>N.O. Switch Qty</b> 0, 1, 2, 3, etc.							

For applications support contact us today.

[sales@edriveactuators.com](mailto:sales@edriveactuators.com)

FB6131